

# Linear Programming Relaxation Approach to Weighted CSP

Tomáš Werner



Center for Machine Perception  
Czech Technical University  
Prague, Czech Republic

- ▶ Notation
- ▶ Part 1: LP relaxation approach of WCSP, following [Schlesinger-1976]
- ▶ Part 2: Algorithms to solve the LP relaxation
- ▶ Part 3: Higher order relaxations

# Notation

$V$	(finite) set of <b>variables</b> , totally ordered
$v \in V$	a single variable
$X_v$	(finite) <b>domain</b> of variable $v \in V$
$x_v \in X_v$	<b>state</b> of variable $v \in V$
$A \subseteq V$	a subset of variables
$X_A = \prod_{v \in A} X_v$	<b>joint domain</b> of variables $A \subseteq V$ (ordered by the order on $V$ )
$x_A \in X_A$	<b>joint state</b> ('tuple', 'configuration') of variables $A \subseteq V$

## Convention: "Implicit restriction"

For  $B \subset A$ , if symbols  $x_A$  and  $x_B$  appear in the same logical expression,  $x_B$  denotes the restriction of joint state  $x_A$  onto variables  $B$ .

$\bar{\mathbb{R}}$  extended reals,  $\bar{\mathbb{R}} = \mathbb{R} \cup \{-\infty\}$   
 $f_A: X_A \rightarrow \bar{\mathbb{R}}$  **constraint** with **scope**  $A \subseteq V$

$2^V$  the set of all subsets of  $V$   
 $\binom{V}{k}$  the set of all  $k$ -element subsets of  $V$

## Definition (Constraint network)

Let  $E \subseteq 2^V$  be a hypergraph. Let each hyperedge  $A \in E$  be assigned a constraint  $f_A: X_A \rightarrow \bar{\mathbb{R}}$ . This collection of constraints is called a **constraint network**.

Denoting  $T(E) = \{ (A, x_A) \mid A \in E, x_A \in X_A \}$ , a constraint network is a mapping

$$\begin{aligned} f : \quad T(E) &\rightarrow \bar{\mathbb{R}} \\ (A, x_A) &\mapsto f_A(x_A) \end{aligned}$$

## Definition (Weighted CSP, WCSP)


Given a constraint network  $f$ , compute the value (and, optionally, a maximiser) of

$$\max_{x_V \in X_V} \sum_{A \in E} f_A(x_A)$$

## Example: A ternary WCSP

Let  $V = (1, 2, 3, 4)$  and  $E = \{(2, 3, 4), (1, 2), (3, 4), (3)\}$ . Then

$$\max_{x_V} \sum_{A \in E} f_A(x_A) = \max_{x_1, x_2, x_3, x_4} [f_{234}(x_2, x_3, x_4) + f_{12}(x_1, x_2) + f_{34}(x_3, x_4) + f_3(x_3)]$$



## Example: A binary WCSP

Let  $E = \binom{V}{1} \cup E'$  with  $E' \subseteq \binom{V}{2}$  (all unary and some binary constraints)


$$\max_{x_V} \sum_{A \in E} f_A(x_A) = \max_{x_V} \left[ \sum_{v \in V} f_v(x_v) + \sum_{vv' \in E'} f_{vv'}(x_v, x_{v'}) \right]$$

## Example: A binary WCSP

Let  $E = \binom{V}{1} \cup E'$  with  $E' \subseteq \binom{V}{2}$  (all unary and some binary constraints)

$$\max_{x_V} \sum_{A \in E} f_A(x_A) = \max_{x_V} \left[ \sum_{v \in V} f_v(x_v) + \sum_{w' \in E'} f_{w'}(x_v, x_{v'}) \right]$$

Microstructure for  $E$  a grid graph and  $X_v = \{1, 2, 3\}$ :




## Example: A binary WCSP

Let  $E = \binom{V}{1} \cup E'$  with  $E' \subseteq \binom{V}{2}$  (all unary and some binary constraints)

$$\max_{x_V} \sum_{A \in E} f_A(x_A) = \max_{x_V} \left[ \sum_{v \in V} f_v(x_v) + \sum_{w' \in E'} f_{w'}(x_v, x_{v'}) \right]$$

Microstructure for  $E$  a grid graph and  $X_v = \{1, 2, 3\}$ :





# Part 1

LP Relaxation of WCSP by [Schlesinger-1976]  
(more precisely, its n-ary generalisation)

- ▶ Formulate two LPs, each yielding an upper bound on WCSP:
  - ▶ The first LP is a continuous relaxation of an integer LP formulation of WCSP
  - ▶ The second LP minimises an upper bound on WCSP by equivalent transformations
- ▶ Show that the two LPs are dual to each other
- ▶ Characterise when the upper bound is tight or minimal

**Note:** LP relaxation of WCSP yielding the same bound as [Schlesinger-1976] was proposed also by other researchers [Koster-1998, Chekuri-2001, Wainwright-2003, Cooper-deGivry-Schiex-2007]. We follow [Schlesinger-76] for its particular simplicity.

# Primal LP

## Joint states as probability distributions

Each hyperedge  $A \in E$  is assigned a function  $\mu_A: X_A \rightarrow \mathbb{R}$  that satisfies:

(non-negativity)  $\mu_A(x_A) \geq 0$   $A \in E; x_A \in X_A$

(normalisation)  $\sum_{x_A} \mu_A(x_A) = 1$   $A \in E$

- Non-negativity and normalisation impose that  $\mu_A$  is a **probability distribution**.

Each hyperedge  $A \in E$  is assigned a function  $\mu_A: X_A \rightarrow \mathbb{R}$  that satisfies:

$$\text{(non-negativity)} \quad \mu_A(x_A) \geq 0 \quad A \in E; x_A \in X_A$$

$$\text{(normalisation)} \quad \sum_{x_A} \mu_A(x_A) = 1 \quad A \in E$$

$$\text{(marginalisation)} \quad \sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B) \quad A, B \in E; B \subset A; x_B \in X_B$$

- ▶ Non-negativity and normalisation impose that  $\mu_A$  is a **probability distribution**.
- ▶ Marginalisation imposes that  $\mu_B$  is the **marginal distribution** of  $\mu_A$ .

# Primal LP

## Joint states as probability distributions

Each hyperedge  $A \in E$  is assigned a function  $\mu_A: X_A \rightarrow \mathbb{R}$  that satisfies:

(non-negativity)  $\mu_A(x_A) \geq 0 \quad A \in E; x_A \in X_A$

(normalisation)  $\sum_{x_A} \mu_A(x_A) = 1 \quad A \in E$

(marginalisation)  $\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B) \quad A, B \in E; B \subset A; x_B \in X_B$

- ▶ Non-negativity and normalisation impose that  $\mu_A$  is a **probability distribution**.
- ▶ Marginalisation imposes that  $\mu_B$  is the **marginal distribution** of  $\mu_A$ .

### Example

Let  $A = (1, 2, 3, 4)$  and  $B = (1, 3)$ . The marginalisation condition reads

$$\mu_{13}(x_1, x_3) = \sum_{x_2, x_4} \mu_{1234}(x_1, x_2, x_3, x_4)$$

# Primal LP

## Joint states as probability distributions

Each hyperedge  $A \in E$  is assigned a function  $\mu_A: X_A \rightarrow \mathbb{R}$  that satisfies:

(non-negativity)  $\mu_A(x_A) \geq 0 \quad A \in E; x_A \in X_A$

(normalisation)  $\sum_{x_A} \mu_A(x_A) = 1 \quad A \in E$

(marginalisation)  $\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B) \quad A, B \in E; B \subset A; x_B \in X_B$

- ▶ Non-negativity and normalisation impose that  $\mu_A$  is a **probability distribution**.
- ▶ Marginalisation imposes that  $\mu_B$  is the **marginal distribution** of  $\mu_A$ .


### Example

Let  $A = (1, 2, 3, 4)$  and  $B = (1, 3)$ . The marginalisation condition reads


$$\mu_{13}(x_1, x_3) = \sum_{x_2, x_4} \mu_{1234}(x_1, x_2, x_3, x_4)$$

**Note:** To couple **all pairs** of overlapping distributions, we assume that  $E$  is **closed under hyperedge intersection** ( $A, B \in E$  implies  $A \cap B \in E$ ).

Example for  $A = (v, v')$  and  $B = (v)$ :



Example for  $A = (v, v')$  and  $B = (v)$ :






# Primal LP

## Meaning of constraints on $\mu$ for a binary problem


Example for  $A = (v, v')$  and  $B = (v)$ :



What happens if the distributions  $\mu$  are **crisp**, i.e.,  $\mu_A(x_A) \in \{0, 1\}$ ?

What happens if the distributions  $\mu$  are **crisp**, i.e.,  $\mu_A(x_A) \in \{0, 1\}$ ?


- ▶ Every distribution  $\mu_A$  represents a **single** joint state.




crisp  $\mu$  satisfying normalisation

What happens if the distributions  $\mu$  are **crisp**, i.e.,  $\mu_A(x_A) \in \{0, 1\}$ ?

- ▶ Every distribution  $\mu_A$  represents a **single** joint state.
- ▶ The marginalisation constraint  $\mu_B(x_B) = \sum_{x_{A \setminus B}} \mu_A(x_A)$  represents the fact that joint state  $\mu_B$  is the **restriction** of joint state  $\mu_A$  to variables  $B \subset A$ .




crisp  $\mu$  satisfying normalisation




crisp  $\mu$  satisfying also marginalisation

What happens if the distributions  $\mu$  are **crisp**, i.e.,  $\mu_A(x_A) \in \{0, 1\}$ ?

- ▶ Every distribution  $\mu_A$  represents a **single** joint state.
- ▶ The marginalisation constraint  $\mu_B(x_B) = \sum_{x_{A \setminus B}} \mu_A(x_A)$  represents the fact that joint state  $\mu_B$  is the **restriction** of joint state  $\mu_A$  to variables  $B \subset A$ .
- ▶ The objective function is given by  $f\mu = \sum_{A \in E} \sum_{x_A} f_A(x_A) \mu_A(x_A)$ .



crisp  $\mu$  satisfying normalisation



crisp  $\mu$  satisfying also marginalisation

### Theorem

Let  $\binom{V}{1} \subseteq E$ .

The WCSP optimum  $\max_{x_V} \sum_{A \in E} f_A(x_A)$  equals to the optimum of the integer LP

$$\begin{aligned} & f\mu \rightarrow \max \\ \text{subject to: } & \mu_A(x_A) \in \{0, 1\} & A \in E, x_A \in X_A \\ & \sum_{x_A} \mu_A(x_A) = 1 & A \in E \\ & \sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B) & A, B \in E, B \subset A, x_B \in X_B \end{aligned}$$


Relaxing  $\mu_A(x_A) \in \{0, 1\}$  to  $\mu_A(x_A) \in [0, 1]$  yields the primal LP.

### Definition

- ▶ Networks  $f$  and  $f'$  are **equivalent** iff they yield the same objective function.
- ▶ A change of  $f$  to an equivalent network is an **equivalent transformation**.

An equivalent transformation is **local** iff it is applied to a triplet  $(A, B, x_B)$  with  $B \subset A$  as follows:

Example for  $A = (v, v')$  and  $B = (v)$ :



# Dual LP

## Equivalent transformations


### Definition

- ▶ Networks  $f$  and  $f'$  are **equivalent** iff they yield the same objective function.
- ▶ A change of  $f$  to an equivalent network is an **equivalent transformation**.

An equivalent transformation is **local** iff it is applied to a triplet  $(A, B, x_B)$  with  $B \subset A$  as follows:

- ▶ add a constant  $\varphi_{A,B}(x_B)$  to weights  $\{f_A(x_A) \mid x_{A \setminus B} \in X_{A \setminus B}\}$

Example for  $A = (v, v')$  and  $B = (v)$ :





# Dual LP

## Equivalent transformations


### Definition

- ▶ Networks  $f$  and  $f'$  are **equivalent** iff they yield the same objective function.
- ▶ A change of  $f$  to an equivalent network is an **equivalent transformation**.

An equivalent transformation is **local** iff it is applied to a triplet  $(A, B, x_B)$  with  $B \subset A$  as follows:

- ▶ add a constant  $\varphi_{A,B}(x_B)$  to weights  $\{f_A(x_A) \mid x_{A \setminus B} \in X_{A \setminus B}\}$
- ▶ subtract the same constant from weight  $f_B(x_B)$

Example for  $A = (v, v')$  and  $B = (v)$ :



- ▶ Assign a constant  $\varphi_{A,B}(x_B)$  to every such triplet  $(A, B, x_B)$  in the network. All these constants together are denoted by  $\varphi$
- ▶ Applying local equivalent transformations on **all** triplets of a network  $f$  yields an equivalent network  $f^\varphi$  given by

$$f_A^\varphi(x_A) = f_A(x_A) + \sum_{B \subset A} \varphi_{A,B}(x_B) - \sum_{B \supset A} \varphi_{B,A}(x_A)$$

- ▶ Problems  $f^\varphi$  for all  $\varphi$  form an **affine subspace** of the space of all networks.
- ▶ For  $f_A(x_A) > -\infty$ , this subspace contains **all** networks equivalent with  $f$ .

## Theorem (Upper bound on WCSP)

$$\underbrace{\max_{x_V} \sum_{A \in E} f_A(x_A)}_{\text{WCSP optimum}} \leq \sum_{A \in E} \max_{x_A} f_A(x_A)$$

The **best upper bound** is found by minimising it over equivalent networks:

$$\min_{\varphi} \sum_{A \in E} \max_{x_A} \left[ \underbrace{f_A(x_A) + \sum_{B \subset A} \varphi_{A,B}(x_B) - \sum_{B \supset A} \varphi_{B,A}(x_A)}_{f_A^{\varphi}(x_A)} \right]$$

This can be written as a linear program

$$\begin{aligned} & \sum_{A \in E} \psi_A \rightarrow \min_{\varphi, \psi} \\ \text{subject to: } & f_A^{\varphi}(x_A) \leq \psi_A \quad A \in E, x_A \in X_A \end{aligned}$$

# When is the upper bound tight?

## Definition

Joint state  $x_A$  of hyperedge  $A \in E$  is called

active	if	$f_A(x_A) = \max_{y_A} f_A(y_A)$
inactive	if	$f_A(x_A) < \max_{y_A} f_A(y_A)$

# When is the upper bound tight?

## Definition

Joint state  $x_A$  of hyperedge  $A \in E$  is called  $\left\{ \begin{array}{ll} \text{active} & \text{if } f_A(x_A) = \max_{y_A} f_A(y_A) \\ \text{inactive} & \text{if } f_A(x_A) < \max_{y_A} f_A(y_A) \end{array} \right.$


## Theorem

*The upper bound is tight iff the (crisp) CSP formed by the active joint states is satisfiable.*

# When is the upper bound tight?

objective function for joint state  $x_V$


$$\sum_{A \in E} f_A(x_A) \leq$$



joint states given by  $x_V$

upper bound

$$\sum_{A \in E} \max_{x_A} f_A(x_A)$$




active joint states

# When is the upper bound tight?

objective function for joint state  $x_V$


$$\sum_{A \in E} f_A(x_A) \leq$$



joint states given by  $x_V$

upper bound

$$\sum_{A \in E} \max_{x_A} f_A(x_A)$$



active joint states

Do they form a satisfiable CSP?

# When is the upper bound tight?


objective function for joint state  $x_V$

$$\sum_{A \in E} f_A(x_A)$$


<

upper bound

$$\sum_{A \in E} \max_{x_A} f_A(x_A)$$



joint states given by  $x_V$



active joint states

Do they form a satisfiable CSP?


No!



# When is the upper bound tight?

objective function for joint state  $x_V$


$$\sum_{A \in E} f_A(x_A) \leq$$



joint states given by  $x_V$

upper bound

$$\sum_{A \in E} \max_{x_A} f_A(x_A)$$




active joint states

Do they form a satisfiable CSP?

# When is the upper bound tight?

objective function for joint state  $x_V$


$$\sum_{A \in E} f_A(x_A)$$



joint states given by  $x_V$

upper bound

$$\sum_{A \in E} \max_{x_A} f_A(x_A)$$




active joint states

Do they form a satisfiable CSP?

Yes!

## The approach summarised



The instances that are solved exactly form a **large, highly non-trivial tractable WCSP subclass**.

$$f\mu \rightarrow \max_{\mu}$$

$$\sum_{A \in E} \psi_A \rightarrow \min_{\varphi, \psi}$$

$$\sum_{x_A \in B} \mu_A(x_A) = \mu_B(x_B)$$

$$\varphi_{A,B}(x_B) \leq 0$$

$$\begin{cases} A, B \in E \\ B \subset A \\ x_B \in X_B \end{cases}$$

$$\sum_{x_A} \mu_A(x_A) = 1$$

$$\psi_A \leq 0$$

$$A \in E$$

$$\mu_A(x_A) \geq 0$$

$$\underbrace{f_A(x_A) + \sum_{B \subset A} \varphi_{A,B}(x_B) - \sum_{B \supset A} \varphi_{B,A}(x_A)}_{f_A^{\varphi}(x_A)} \leq \psi_A$$

$$\begin{cases} A \in E \\ x_A \in X_A \end{cases}$$

$$f\mu \rightarrow \max_{\mu}$$

$$\sum_{A \in E} \psi_A \rightarrow \min_{\varphi, \psi}$$

$$\sum_{x_A \in B} \mu_A(x_A) = \mu_B(x_B)$$

$$\varphi_{A,B}(x_B) \leq 0$$

$$\begin{cases} A, B \in E \\ B \subset A \\ x_B \in X_B \end{cases}$$

$$\sum_{x_A} \mu_A(x_A) = 1$$

$$\psi_A \leq 0$$

$$A \in E$$

$$\mu_A(x_A) \geq 0$$

$$\underbrace{f_A(x_A) + \sum_{B \subset A} \varphi_{A,B}(x_B) - \sum_{B \supset A} \varphi_{B,A}(x_A)}_{f_A^{\varphi}(x_A)} \leq \psi_A$$

$$\begin{cases} A \in E \\ x_A \in X_A \end{cases}$$

$$f\mu \rightarrow \max_{\mu}$$

$$\psi 1 \rightarrow \min_{\varphi, \psi}$$

$$M\mu = 0$$

$$\varphi \leq 0$$

$$N\mu = 1$$

$$\psi \leq 0$$

$$\mu \geq 0$$

$$\varphi M + \psi N \geq f$$

$$f\mu \rightarrow \max_{\mu}$$

$$\sum_{A \in E} \psi_A \rightarrow \min_{\varphi, \psi}$$

$$\sum_{x_A \in B} \mu_A(x_A) = \mu_B(x_B)$$

$$\varphi_{A,B}(x_B) \leq 0$$

$$\begin{cases} A, B \in E \\ B \subset A \\ x_B \in X_B \end{cases}$$

$$\sum_{x_A} \mu_A(x_A) = 1$$

$$\psi_A \leq 0$$

$$A \in E$$

$$\mu_A(x_A) \geq 0$$

$$\underbrace{f_A(x_A) + \sum_{B \subset A} \varphi_{A,B}(x_B) - \sum_{B \supset A} \varphi_{B,A}(x_A)}_{f_A^{\varphi}(x_A)} \leq \psi_A$$

$$\begin{cases} A \in E \\ x_A \in X_A \end{cases}$$

$$f\mu \rightarrow \max_{\mu}$$

$$\psi 1 \rightarrow \min_{\varphi, \psi}$$

$$M\mu = 0$$

$$\varphi \leq 0$$

$$N\mu = 1$$

$$\psi \leq 0$$

$$\mu \geq 0$$


$$\varphi M + \psi N \geq f$$

**primal program**


**dual program**

# Hydraulic model of the LP pair [Schlesinger-Kovalevsky-1970's]

top view



side view



- ▶  $\mu_A(x_A)$  correspond to **forces** in forks and **presures** in tanks.
- ▶  $\varphi_{A,B}(x_A)$  correspond to **displacements** of the pistons.
- ▶ The upper bound correspond to **potential energy** of the device.

$$\begin{array}{ll} f\mu \rightarrow \max & \psi 1 \rightarrow \min \\ M\mu = 0 & \varphi \leq 0 \\ N\mu = 1 & \psi \leq 0 \\ \mu \geq 0 & \varphi M + \psi N \geq f \end{array}$$

Feasible  $\mu$  and  $(\varphi, \psi)$  satisfy:

weak duality:  $f\mu \leq \psi 1$

strong duality:  $\mu$  and  $(\varphi, \psi)$  are optimal iff  $f\mu = \psi 1$

complementary slackness:  $\mu$  and  $(\varphi, \psi)$  are optimal iff  $(\varphi M + \psi N - f)\mu = 0$



# Complementary slackness in WCSP

Expression  $(\varphi M + \psi N - f)\mu = 0$  reads

$$\forall A \in E, x_A \in X_A : \left[ \max_{y_A} f_A^\varphi(y_A) - f_A^\varphi(x_A) \right] \mu_A(x_A) = 0$$

which means:

## Theorem (Complementary slackness in WCSP)

Let  $\mu$  be primal-feasible. The primal and dual LPs are simultaneously optimal iff every joint state  $x_A$  of every hyperedge  $A \in E$  satisfies the implication

$$(A, x_A) \text{ is inactive} \implies \mu_A(x_A) = 0$$

## Definition

The CSP formed by active joint states is **relaxed-satisfiable** iff there exists a feasible  $\mu$  for which the above implication holds.

## Theorem

A network  $f$  has the least upper bound iff the CSP formed by active joint states is relaxed-satisfiable.

## Three levels of consistency of crisp CSP

A crisp CSP represented by  $\sigma: T(E) \rightarrow \{0,1\}$

is relaxed satisfiable

iff there exists  $\mu \leq \sigma$  satisfying

$$\begin{aligned}\mu_A(x_A) &\geq 0 \\ \sum_{x_A} \mu_A(x_A) &= 1 \\ \sum_{x_{A \setminus B}} \mu_A(x_A) &= \mu_B(x_B)\end{aligned}$$

# Three levels of consistency of crisp CSP

A crisp CSP represented by  $\sigma: T(E) \rightarrow \{0, 1\}$

is satisfiable

is relaxed satisfiable

iff there exists  $\mu \leq \sigma$  satisfying

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

$$\begin{aligned} \mu_A(x_A) &\geq 0 \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

# Three levels of consistency of crisp CSP

A crisp CSP represented by  $\sigma: T(E) \rightarrow \{0, 1\}$

is satisfiable

is relaxed satisfiable

has a non-empty  
pairwise consistency closure

iff there exists  $\mu \leq \sigma$  satisfying

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

$$\begin{aligned} \mu_A(x_A) &\geq 0 \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \max_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\max_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

# Three levels of consistency of crisp CSP

A crisp CSP represented by  $\sigma: T(E) \rightarrow \{0, 1\}$

is satisfiable  $\implies$  is relaxed satisfiable  $\implies$  has a non-empty pairwise consistency closure

iff there exists  $\mu \leq \sigma$  satisfying

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

$$\begin{aligned} \mu_A(x_A) &\geq 0 \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \max_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\max_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

# Three levels of consistency of crisp CSP

A crisp CSP represented by  $\sigma: T(E) \rightarrow \{0, 1\}$

is satisfiable  $\implies$  is relaxed satisfiable  $\implies$  has a non-empty pairwise consistency closure

iff there exists  $\mu \leq \sigma$  satisfying

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

upper bound is tight

$$\begin{aligned} \mu_A(x_A) &\geq 0 \\ \sum_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$


upper bound is minimal

$$\begin{aligned} \mu_A(x_A) &\in \{0, 1\} \\ \max_{x_A} \mu_A(x_A) &= 1 \end{aligned}$$

$$\max_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

# Pairwise consistency is insufficient for relaxed satisfiability


## Primal argument



- This is an arc consistent CSP.

# Pairwise consistency is insufficient for relaxed satisfiability

## Primal argument




- ▶ This is an arc consistent CSP.
- ▶ But there exists no  $\mu$  on allowed joint states satisfying non-negativity, normalisation and marginalisation condition.



# Pairwise consistency is insufficient for relaxed satisfiability


## Primal argument



- ▶ This is an arc consistent CSP.
- ▶ But there exists no  $\mu$  on allowed joint states satisfying non-negativity, normalisation and marginalisation condition.

# Pairwise consistency is insufficient for relaxed satisfiability


## Dual argument



There exists an equivalent transformation of  $f$  that makes arc consistent closure empty. Hence, the upper bound can be decreased.

# Pairwise consistency is insufficient for relaxed satisfiability

## Dual argument



There exists an equivalent transformation of  $f$  that makes arc consistent closure empty. Hence, the upper bound can be decreased.

# Part 2

## Algorithms to Decrease the Upper Bound

# The problem of solving LP relaxation of WCSP

The dual LP more suitable to solve than the primal LP because

- ▶ it has fewer variables,
- ▶ all the optimal solutions are encoded in active joint states.

We need to solve

$$\min_{\varphi} \sum_{A \in E} \max_{x_A} \left[ \underbrace{f_A(x_A) + \sum_{B \subset A} \varphi_{A,B}(x_B) - \sum_{B \supset A} \varphi_{B,A}(x_A)}_{f_A^{\varphi}(x_A)} \right]$$

which is an **unconstrained minimisation problem**  
with **convex** and **nonsmooth (piecewise linear)** objective function.

- ▶ Restriction on the algorithm: space complexity must be **linear** in the number of variables  $\varphi_{A,B}(x_B)$ .

## Survey of existing approaches

- ▶ Algorithms that make active joint states pairwise/arc consistent  
(more efficient, but not guaranteed to find global minimum of upper bound)
- ▶ Algorithms that find global minimum of the upper bound  
(typically less efficient)

- ▶ Algorithms that make active joint states pairwise/arc consistent (more efficient, but not guaranteed to find global minimum of upper bound)
  - ▶ Max-sum diffusion [Koval-Kovalevsky-1976, Flach-2000, Werner-2008]
  - ▶ Sequential Tree-reweighted Message Passing (TRW-S) [Wainwright-etal-2003, Kolmogorov-2005]
  - ▶ Augmenting DAG algorithm [Koval-Schlesinger-1976]  
virtual arc consistency algorithm [Cooper-deGivry-Schiex-2006-8]
- ▶ Algorithms that find global minimum of the upper bound (typically less efficient)

- ▶ Algorithms that make active joint states pairwise/arc consistent (more efficient, but not guaranteed to find global minimum of upper bound)
  - ▶ Max-sum diffusion [Koval-Kovalevsky-1976, Flach-2000, Werner-2008]
  - ▶ Sequential Tree-reweighted Message Passing (TRW-S) [Wainwright-etal-2003, Kolmogorov-2005]
  - ▶ Augmenting DAG algorithm [Koval-Schlesinger-1976]  
virtual arc consistency algorithm [Cooper-deGivry-Schiex-2006-8]

These algorithms yield exact solution for **supermodular WCSPs**!

- ▶ Algorithms that find global minimum of the upper bound (typically less efficient)



- ▶ Algorithms that make active joint states pairwise/arc consistent (more efficient, but not guaranteed to find global minimum of upper bound)
  - ▶ Max-sum diffusion [Koval-Kovalevsky-1976, Flach-2000, Werner-2008]
  - ▶ Sequential Tree-reweighted Message Passing (TRW-S) [Wainwright-etal-2003, Kolmogorov-2005]
  - ▶ Augmenting DAG algorithm [Koval-Schlesinger-1976]  
virtual arc consistency algorithm [Cooper-deGivry-Schiex-2006-8]

These algorithms yield exact solution for **supermodular WCSPs**!

- ▶ Algorithms that find global minimum of the upper bound (typically less efficient)
  - ▶ Subgradient descent [Schlesinger-Giginjak-2007, Komodakis-etal-2007]
  - ▶ Smoothing methods [Werner-2007, Johnson-etal-2007]


Max-sum diffusion repeats this simple operation:

- ▶ On a triplet  $(A, B, x_B)$  with  $B \subset A$ , apply the local equivalent transformation that makes satisfied the equality  $\max_{x_{A \setminus B}} f_A(x_A) = f_B(x_B)$

Max-sum diffusion repeats this simple operation:

- ▶ On a triplet  $(A, B, x_B)$  with  $B \subset A$ , apply the local equivalent transformation that makes satisfied the equality  $\max_{x_{A \setminus B}} f_A(x_A) = f_B(x_B)$


Example for  $A = (v, v')$  and  $B = (v)$ :



Max-sum diffusion repeats this simple operation:

- ▶ On a triplet  $(A, B, x_B)$  with  $B \subset A$ , apply the local equivalent transformation that makes satisfied the equality  $\max_{x_{A \setminus B}} f_A(x_A) = f_B(x_B)$

Example for  $A = (v, v')$  and  $B = (v)$ :



### Algorithm: Max-sum diffusion

```
1: loop
2:   for  $(A, B)$  such that  $A \in E, B \in E, B \subset A$  do
3:     for  $x_B \in X_B$  do
4:        $\varphi_{A,B}(x_B) \leftarrow \varphi_{A,B}(x_B) + [f_B^\varphi(x_B) - \max_{x_{A \setminus B}} f_A^\varphi(x_A)]/2$ 
5:     end for
6:   end for
7: end loop
```

Properties of the algorithm:

- ▶ It monotonically decreases the upper bound.
- ▶ (Conjecture) It converges to a fixed point when  $\max_{x_{A \setminus B}} f_A^\varphi(x_A) = f_B^\varphi(x_B)$  holds for all triplets  $(A, B, x_B)$  with  $B \subset A$ .
- ▶ At a fixed point, the CSP formed by active joint states is pairwise consistent.


# Max-sum diffusion

## Interpretation as a coordinate descent

Max-sum diffusion can be seen as a **coordinate descent** to decrease the upper bound:

- ▶ Minimise over a single free variable, keeping the other variables fixed.
- ▶ Iterate this for different free variables.

But coordinate descent is not guaranteed to find the global minimum of a convex **nonsmooth** function!



Point  $(x^*, y^*)$  is not a global minimum despite it is minimal separately in each coordinate.

# Tree-reweighted Message Passing [Wainwright-etal-2003, Kolmogorov-2005]

## Decomposing WCSP to tractable subproblems

- ▶ Let  $f^k$  denote a network with variables  $V^k \subseteq V$  and hypergraph  $E^k \subseteq 2^{V^k}$ .
- ▶ Let  $\{f^k \mid k \in K\}$  be a collection of networks satisfying

$$f_A(x_A) = \sum_{k \mid A \in E^k} f_A^k(x_A) \quad \forall A \in E, x_A \in X_A$$

- ▶ The objective function  $F^k: X_{V^k} \rightarrow \bar{\mathbb{R}}$  of network  $f^k$  is  $F^k(x_{V^k}) = \sum_{A \in E^k} f_A^k(x_A)$
- ▶ Swapping maximum and sum yields an upper bound on WCSP:

$$\max_{x_V} \sum_{A \in E} f_A(x_A) = \max_{x_V} \sum_k F^k(x_{V^k}) \leq \sum_k \max_{x_{V^k}} F^k(x_{V^k})$$


### Minimising the upper bound

Minimise  $\sum_k \max_{x_{V^k}} \sum_{A \in E^k} f_A^k(x_A)$  over collections  $\{f^k \mid k \in K\}$  subject to

$$f_A(x_A) = \sum_{k \mid A \in E^k} f_A^k(x_A)$$

# Tree-reweighted Message Passing [Wainwright-etal-2003, Kolmogorov-2005]

Example: Decomposing a grid graph to rows and columns




- ▶ Max-marginals of the row and column subproblems are iteratively equalised (like in max-sum diffusion) in the unary constraints.
- ▶ The row and column subproblems are solved efficiently by dynamic programming, in an **incremental** (hence efficient) way.




# Tree-reweighted Message Passing [Wainwright-etal-2003, Kolmogorov-2005]

Equivalence to the approach [Schlesinger-1976] and max-sum diffusion


- ▶ Decomposing WCSP to subproblems is equivalent to approach by [Schlesinger-1976]. They can be translated to each other:
  - ▶ Expressing [Schlesinger-1976] by decomposition: Hypergraphs  $E^k$  are individual hyperedges  $A \in E$ .
  - ▶ Expressing decomposition by [Schlesinger-1976]: Each constraint  $f_A$  is itself a tractable WCSP,  $F^k$ .
- ▶ For binary problems, decomposing WCSP to trees yields (under mild assumptions) the same relaxation as the max-sum diffusion. But more efficient, especially on images.
- ▶ It is not straightforward to extend this efficiency to non-binary networks.




Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).




Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).




Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).




Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).



Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).




Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).



Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).


- If all states in any variable are deleted, the upper bound cannot be minimal.





Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).

- If all states in any variable are deleted, the upper bound cannot be minimal. Then, it can be decreased by pushing weights along (a subgraph of) the DAG.




Run arc consistency algorithm on the active joint states. During this, remember pointers to causes of deletion. The pointers form an **directed acyclic graph** (DAG).


- ▶ If all states in any variable are deleted, the upper bound cannot be minimal. Then, it can be decreased by pushing weights along (a subgraph of) the DAG.
- ▶ If a non-empty arc consistency closure is found, halt.

## Example WCSP: Syntactic image analysis

Find the image containing non-overlapping rectangles, nearest to input image!



input image




output image


## Example WCSP: Syntactic image analysis

Find the image containing non-overlapping rectangles, nearest to input image!

- ▶ Variables  $V$  are pixels, hypergraph  $E$  is the image grid.



input image



output image


## Example WCSP: Syntactic image analysis

Find the image containing non-overlapping rectangles, nearest to input image!


- ▶ Variables  $V$  are pixels, hypergraph  $E$  is the image grid.
- ▶ Variable domains  $X_v = \{E, I, L, R, T, B, TL, TR, BL, BR\}$  are **syntactic parts** of a rectangle.

E	E	E	E	E	E	E
E	TL	T	T	T	TR	E
E	L	I	I	I	R	E
E	L	I	I	I	R	E
E	BL	B	B	B	BR	E
E	E	E	E	E	E	E

hidden states = syntactic parts



input image



output image


## Example WCSP: Syntactic image analysis

Find the image containing non-overlapping rectangles, nearest to input image!


- ▶ Variables  $V$  are pixels, hypergraph  $E$  is the image grid.
- ▶ Variable domains  $X_v = \{E, I, L, R, T, B, TL, TR, BL, BR\}$  are **syntactic parts** of a rectangle.
- ▶ Unary constraint  $f_v(x_v)$  quantifies agreement of intensity of state  $x_v$  and intensity of input pixel  $v$ .

E	E	E	E	E	E	E
E	TL	T	T	T	TR	E
E	L	I	I	I	R	E
E	L	I	I	I	R	E
E	BL	B	B	B	BR	E
E	E	E	E	E	E	E

hidden states = syntactic parts  
observed states = {black,white}



input image



output image


## Example WCSP: Syntactic image analysis

Find the image containing non-overlapping rectangles, nearest to input image!


- ▶ Variables  $V$  are pixels, hypergraph  $E$  is the image grid.
- ▶ Variable domains  $X_v = \{E, I, L, R, T, B, TL, TR, BL, BR\}$  are **syntactic parts** of a rectangle.
- ▶ Unary constraint  $f_v(x_v)$  quantifies agreement of intensity of state  $x_v$  and intensity of input pixel  $v$ .
- ▶ Binary constraint  $f_{vv'}(x_v, x_{v'})$  equals 0 if syntactic parts  $x_v$  and  $x_{v'}$  are allowed to neighbor and  $-\infty$  otherwise.

E	E	E	E	E	E	E
E	TL	T	T	T	TR	E
E	L	I	I	I	R	E
E	L	I	I	I	R	E
E	BL	B	B	B	BR	E
E	E	E	E	E	E	E

hidden states = syntactic parts  
observed states = {black,white}



input image



output image

## Example: Binary WCSP with a global constraint [Werner-2008]

- ▶  $E = \binom{V}{1} \cup E' \cup \{V\}$  where  $E' \subseteq \binom{V}{2}$ ,  $X_v = \{\text{white}, \text{black}\}$ .
- ▶ Unary constraint  $f_v$  quantifies agreement with intensity of input pixel  $v$ .
- ▶ Binary constraints  $f_{vv'}$  penalise transition between black and white pixels.
- ▶ Global constraint  $f_V(x_V)$  is: 0 if  $x_V$  contains  $n$  black pixels and  $-\infty$  otherwise.

**Interpretation:** Find minimum  $st$ -cut in a graph such that the number of pixels in the first partition equals  $n$  (NP-hard).

- ▶ Max-sum diffusion enforces generalised arc consistency of active joint states.
- ▶ Equalising max-marginals between  $f_v$  and  $f_V$  seen as a **soft global propagator**.



input



$n$ required:	2000	3000	4000	5000	5368	6000	7000	8000	9000
$n$ achieved:	2008	3004	4011	5006	5368	6004	7024	7982	9032



# Supermodular problems

Let each domain  $X_v$  be totally ordered. A function  $f_A$  is supermodular if

$$f_A(x_A \wedge y_A) + f_A(x_A \vee y_A) \geq f_A(x_A) + f_A(y_A)$$

for any  $x_A, y_A \in X_A$ , where  $\wedge$  ( $\vee$ ) denotes the elementwise minimum (maximum).

Theorem ([Schlesinger-Flach-00] for binary case, [Werner-2008] for non-binary case)

*Let  $f_A$  be supermodular for each  $A \in E$ . Finding an equivalent network whose active joint states are generalised arc consistent solves the WCSP  $f$  exactly.*


## Proof

- ▶ Equivalent transformations preserve supermodularity.
- ▶ The maximisers of a supermodular function on a distributive lattice form a sublattice of this lattice [Topkis78]. Hence, the active joint states of each constraint form a lattice. Hence, all active joint states form a well-known tractable CSP [Jeavons-Cooper-95] (lattice CSP).
- ▶ Generalised arc consistency suffices for a lattice CSP to be satisfiable.

Before, [Cooper-2008] showed that the LP relaxation is tight for non-binary supermodular WCSPs. Our statement is stronger and the proof is simpler.

# Supermodular problems


## Example for binary networks




$$x \leq x', y \leq y' \quad \Rightarrow \quad f_{vv'}(x, x') + f_{vv'}(y, y') \geq f_{vv'}(x, y') + f_{vv'}(y, x')$$

# Supermodular problems

## Example for binary networks




$$x \leq x', y \leq y' \implies f_{vv'}(x, x') + f_{vv'}(y, y') \geq f_{vv'}(x, y') + f_{vv'}(y, x')$$




# Supermodular problems

## Example for binary networks




$$x \leq x', y \leq y' \implies f_{vv'}(x, x') + f_{vv'}(y, y') \geq f_{vv'}(x, y') + f_{vv'}(y, x')$$




# Supermodular problems

## Example for binary networks



$$x \leq x', y \leq y' \implies f_{vv'}(x, x') + f_{vv'}(y, y') \geq f_{vv'}(x, y') + f_{vv'}(y, x')$$



# Subgradient descent

Well-known approach to minimise nonsmooth convex functions [Shor-1979].

## Definition (Subgradient)

Let  $f: \mathbb{R}^n \rightarrow \mathbb{R}$  be a convex function. A vector  $g(x_0) \in \mathbb{R}^n$  is a **subgradient** of  $f$  at point  $x_0$  iff  $g^\top(x - x_0) \leq f(x) - f(x_0)$  for all  $x \in \mathbb{R}^n$ .

## Theorem (Subgradient descent)

Let  $f: \mathbb{R}^n \rightarrow \mathbb{R}$  be a convex function. Let  $\{\alpha_i\}_{i=0}^\infty$  be a sequence of positive numbers that converge to zero but their partial sums converge to infinity. For any initial point  $x_0$ , the sequence

$$x_{i+1} = x_i - \alpha_i g(x_i)$$

converges to  $\min_{x \in \mathbb{R}^n} f(x)$ .

Apply gradient descent to minimising the WCSP upper bound

[Schlesinger-Giginjak-2007, Komodakis-et al-2007]:

- ▶ Converges (**non-monotonically**) to the global minimum of the upper bound.
- ▶ Inefficient if applied to a decomposition to individual hyperedges.
- ▶ Efficient if applied to a decomposition to longer trees/chains.

# Smoothing methods

- ▶ Let  $f_\beta: \mathbb{R}^n \rightarrow \mathbb{R}$  be a smooth convex function for every  $\beta > 0$ .
- ▶ With increasing  $\beta$ , let  $f_\beta$  approach a nonsmooth convex function  $f_\infty$ .
- ▶ The sequence  $\min_{x \in \mathbb{R}^n} f_\beta(x)$  converges to  $\min_{x \in \mathbb{R}^n} f_\infty(x)$ .

- 1:  $\beta \leftarrow 1$
- 2: **loop**
- 3:   Minimise  $f_\beta$  by coordinate descent.
- 4:   Increase  $\beta$ .
- 5: **end loop**

An example [Werner-2007, Johnson-et al-2007]:

- ▶ Approach crisp maximum by a sequence of soft maxima:

$$\max\{x, y\} = \lim_{\beta \rightarrow \infty} \frac{1}{\beta} \log(e^{\beta x} + e^{\beta y})$$

Minimising the smoothed upper bound leads to **geometric programming**.

- ▶ Not very practical (in my experience) because of the two nested loops in the algorithm.

# Part 3

## Higher Order Polyhedral Relaxations



## Adding zero constraints

Let  $f$  be a network with hypergraph  $E$ . Let  $A \notin E$ . Add constraint  $f_A \equiv 0$  to  $f$ .

### Theorem

*By adding a zero constraint to a network, the optimal value of the LP pair*

- ▶ *never increases*
- ▶ *for some instances, strictly decreases.*

### Proof, by primal argument

- ▶ The primal objective function is preserved.
- ▶ The new primal feasible set is a strict subset of the old one.

### Proof, by dual argument

- ▶ The dual objective function (i.e., the upper bound) is preserved.
- ▶ New equivalent transformations are enabled and no existing ones disabled.  
Hence, the new dual feasible set is a strict superset of the old one.

The proofs are imprecise because the dimensions of the old and new feasible sets are different. Let us be more precise...

# Relaxation is given by marginalisation conditions

## primal program

$$f\mu \rightarrow \max$$

$$\mu_A(x_A) \geq 0$$

$$\sum_{x_A} \mu_A(x_A) = 1$$

## dual program

$$\sum_{A \in E} \psi_A \rightarrow \min$$

$$f_A(x_A) \leq \psi_A$$

$$\psi_A \leq 0$$

$$A \subseteq V, x_A \in X_A$$

$$A \subseteq V$$

- Suppose that all possible (i.e., for all  $A \subseteq V$ ) zero constraints are added but marginalisation conditions are omitted. The optimal value of the LP pair is

$$\sum_{A \subseteq V} \max_{x_A} f_A(x_A) = \sum_{A \in E} \max_{x_A} f_A(x_A)$$

# Relaxation is given by marginalisation conditions

## primal program

$$f\mu \rightarrow \max$$

$$\mu_A(x_A) \geq 0$$

$$\sum_{x_A} \mu_A(x_A) = 1$$

$$\sum_{x_{A \setminus B}} \mu_A(x_A) = \mu_B(x_B)$$

## dual program

$$\sum_{A \in E} \psi_A \rightarrow \min$$

$$f_A^\varphi(x_A) \leq \psi_A$$

$$\psi_A \leq 0$$

$$\varphi_{A,B}(x_B) \leq 0$$

$$A \subseteq V, x_A \in X_A$$

$$A \subseteq V$$

$$(A, B) \in J, x_B \in X_B$$

- Suppose that all possible (i.e., for all  $A \subseteq V$ ) zero constraints are added but marginalisation conditions are omitted. The optimal value of the LP pair is

$$\sum_{A \subseteq V} \max_{x_A} f_A(x_A) = \sum_{A \in E} \max_{x_A} f_A(x_A)$$

- Couple distribution pairs  $(\mu_A, \mu_B)$  for  $(A, B) \in J$  by marginalisation, where


$$J \subseteq I(2^V) = \{(A, B) \mid B \subset A \subseteq V\} = \text{the inclusion relation on } 2^V$$

Now, tightness of the relaxation is determined by  $J$  alone!

Zero constraints not participating in  $J$  are superfluous.


## The same graphically...

- ▶ The set  $2^V$  of all subsets (except  $\emptyset$ ) of  $V = (1, 2, 3, 4)$ .




## The same graphically...

- ▶ The set  $2^V$  of all subsets (except  $\emptyset$ ) of  $V = (1, 2, 3, 4)$ .
- ▶ Inclusion relation  $\subseteq$  ( $2^V$ ).




## The same graphically...

- ▶ The set  $2^V$  of all subsets (except  $\emptyset$ ) of  $V = (1, 2, 3, 4)$ .
- ▶ Inclusion relation  $I(2^V)$ .
- ▶ Non-zero constraints, given by hypergraph  $E$ .




## The same graphically...

- ▶ The set  $2^V$  of all subsets (except  $\emptyset$ ) of  $V = (1, 2, 3, 4)$ .
- ▶ Inclusion relation  $I(2^V)$ .
- ▶ Non-zero constraints, given by hypergraph  $E$ .
- ▶ Imposing marginalisations  $J = I(E)$  yields the ordinary LP relaxation.



## The same graphically...

- ▶ The set  $2^V$  of all subsets (except  $\emptyset$ ) of  $V = (1, 2, 3, 4)$ .
- ▶ Inclusion relation  $I(2^V)$ .
- ▶ Non-zero constraints, given by hypergraph  $E$ .
- ▶ Imposing marginalisations  $J = I(E)$  yields the ordinary LP relaxation.
- ▶ Adding these three pairs  $(A, B)$  to  $J$  tightens the relaxation.  
This requires adding zero constraint  $f_{124} \equiv 0$ .





# Hierarchy of polyhedral relaxations

$J_1 \subseteq J_2$  implies that relaxation  $J_1$  is not tighter than  $J_2$ . Therefore:

## Theorem

All possible sets  $J \subseteq I(2^V)$  form a **hierarchy of relaxations**, partially ordered by the inclusion relation on  $I(2^V)$ .

In particular:


$J = \emptyset$       the weakest relaxation  
(the sum of independent maxima of all the constraints).

$J = I(E)$       the ordinary LP relaxation [Schlesinger-76, other works...]

$J = I(2^V)$       the exact solution  
(the same as adding the single zero constraint  $f_V \equiv 0$ )

## Example: Adding zero 4-cycle constraints to binary problems

- ▶ Randomly draw instances of a binary problem from an instance type.
- ▶ Count the number of instances solved exactly by an LP relaxation.
- ▶ Two relaxations tested:
  - ▶ Plain LP relaxation without zero constraints




without zero constraints

type	image side	$ X_v $	$r_{\text{plain}}$
random	15	5	0.01
random	25	3	0.00
random	100	3	0.00
Potts	15	5	0.79
Potts	25	5	0.48
Potts	100	5	0.00
lines	10	4	0.72
lines	25	4	0.00
curve	10	9	0.17
curve	15	9	0.00
curve	25	9	0.00
Pi	15	5	0.00

## Example: Adding zero 4-cycle constraints to binary problems

- ▶ Randomly draw instances of a binary problem from an instance type.
- ▶ Count the number of instances solved exactly by an LP relaxation.
- ▶ Two relaxations tested:
  - ▶ Plain LP relaxation without zero constraints
  - ▶ LP relaxation augmented by 4-ary zero constraints on neighboring variables.



with zero constraints

type	image side	$ X_v $	$r_{\text{plain}}$	$r_{\text{4cycle}}$
random	15	5	0.01	1.00
random	25	3	0.00	0.98
random	100	3	0.00	0.72
Potts	15	5	0.79	0.99
Potts	25	5	0.48	0.98
Potts	100	5	0.00	0.81
lines	10	4	0.72	0.88
lines	25	4	0.00	0.00
curve	10	9	0.17	0.65
curve	15	9	0.00	0.24
curve	25	9	0.00	0.00
Pi	15	5	0.00	0.82

## Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

## Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

Cutting plane algorithm for general ILP (in primal space)

# Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

Cutting plane algorithm for general ILP (in primal space)

1:  $P' \leftarrow P$

# Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

## Cutting plane algorithm for general ILP (in primal space)

- 1:  $P' \leftarrow P$
- 2: **loop**
- 3: Find a maximiser  $\mu^*$  of  $\max \{ f\mu \mid \mu \in P' \}$ .
- 6: **end loop**

# Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

## Cutting plane algorithm for general ILP (in primal space)

- 1:  $P' \leftarrow P$
- 2: **loop**
- 3: Find a maximiser  $\mu^*$  of  $\max \{ f\mu \mid \mu \in P' \}$ .
- 4: Find a half-space  $H$  such that  $\mu^* \notin H \supseteq P \cap \mathbb{Z}^n$ . If none exists, halt.
- 6: **end loop**



# Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

## Cutting plane algorithm for general ILP (in primal space)

- 1:  $P' \leftarrow P$
- 2: **loop**
- 3: Find a maximiser  $\mu^*$  of  $\max \{ f\mu \mid \mu \in P' \}$ .
- 4: Find a half-space  $H$  such that  $\mu^* \notin H \supseteq P \cap \mathbb{Z}^n$ . If none exists, halt.
- 5:  $P' \leftarrow P' \cap H$
- 6: **end loop**

# Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

Cutting plane algorithm for general ILP (in primal space)

Cutting plane algorithm for WCSP (in dual space)

## Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

### Cutting plane algorithm for general ILP (in primal space)

- 1:  $P' \leftarrow P$
- 2: **loop**
- 3: Find a maximiser  $\mu^*$  of  $\max \{ f\mu \mid \mu \in P' \}$ .
- 6: **end loop**

### Cutting plane algorithm for WCSP (in dual space)

- 1: **loop**
- 2: Find the equivalent network with the least upper bound.
- 5: **end loop**

## Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .

### Cutting plane algorithm for general ILP (in primal space)

- 1:  $P' \leftarrow P$
- 2: **loop**
- 3: Find a maximiser  $\mu^*$  of  $\max \{ f\mu \mid \mu \in P' \}$ .
- 4: Find a half-space  $H$  such that  $\mu^* \notin H \supseteq P \cap \mathbb{Z}^n$ . If none exists, halt.
- 6: **end loop**

### Cutting plane algorithm for WCSP (in dual space)

- 1: **loop**
- 2: Find the equivalent network with the least upper bound.
- 3: Find  $A \notin E$  such that the CSP formed by active joint states restricted on hypergraph  $E \cap 2^A$  is **unsatisfiable**. If none exists, halt.
- 5: **end loop**

## Cutting plane algorithm

Consider the LP relaxation  $\max \{ f\mu \mid \mu \in P \}$  of ILP  $\max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \}$ .


### Cutting plane algorithm for general ILP (in primal space)

- 1:  $P' \leftarrow P$
- 2: **loop**
- 3: Find a maximiser  $\mu^*$  of  $\max \{ f\mu \mid \mu \in P' \}$ .
- 4: Find a half-space  $H$  such that  $\mu^* \notin H \supseteq P \cap \mathbb{Z}^n$ . If none exists, halt.
- 5:  $P' \leftarrow P' \cap H$
- 6: **end loop**


### Cutting plane algorithm for WCSP (in dual space)

- 1: **loop**
- 2: Find the equivalent network with the least upper bound.
- 3: Find  $A \notin E$  such that the CSP formed by active joint states restricted on hypergraph  $E \cap 2^A$  is **unsatisfiable**. If none exists, halt.
- 4:  $f_A \leftarrow 0$ ;  $E \leftarrow E \cup \{A\}$
- 5: **end loop**


## Example run of cutting plane algorithm



## Example run of cutting plane algorithm




## Example run of cutting plane algorithm






## Example run of cutting plane algorithm



## Example run of cutting plane algorithm




LP relaxation is a common approach to combinatorial optimisation problems:

$$\begin{array}{ccc} & \text{integer LP} & \text{LP relaxation} \\ \max \{ f\mu \mid \mu \in \underbrace{\text{conv}(P \cap \mathbb{Z}^n)}_{\substack{\text{integral hull} \\ \text{of } P}} \} & = \max \{ f\mu \mid \mu \in P \cap \mathbb{Z}^n \} & \leq \max \{ f\mu \mid \mu \in P \} \end{array}$$

- ▶  $P$  is a convex polyhedron with a tractable number of facets.
- ▶ For NP-hard ILPs,  $\text{conv}(P \cap \mathbb{Z}^n)$  has much more facets than  $P$  and they cannot be described in a 'short' way. Facets of  $\text{conv}(P \cap \mathbb{Z}^n)$  that are not facets of  $P$  are good cutting planes.
- ▶ All vertices of  $\text{conv}(P \cap \mathbb{Z}^n)$  are integral while  $P$  may have also fractional vertices.

# Integral hull of WCSP = marginal polytope

Integral hull of WCSP is the set



Definition (Marginal polytope [Wainwright-et-al-2003])

**Marginal polytope** (associated with hypergraph  $E \subseteq 2^V$  and domains  $\{X_V\}$ ) is a set of mappings  $\mu: T(E) \rightarrow [0, 1]$  defined as follows:  $\mu$  belongs to the marginal polytope iff there exists a function  $\mu_V: X_V \rightarrow [0, 1]$  such that  $\sum_{x_V} \mu_V(x_V) = 1$  and

$$\forall A \in E, x_A \in X_A : \sum_{x_{V \setminus A}} \mu_V(x_V) = \mu_A(x_A)$$

That is,  $\mu$  is a set of **valid marginals** of some global distribution  $\mu_V$ .

Theorem

*Marginal polytope is the integral hull of WCSP.*